

FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.

1300 I STREET, N. W.
WASHINGTON, DC 20005-3315

202 • 408 • 4000
FACSIMILE 202 • 408 • 4400

WRITER'S DIRECT DIAL NUMBER:

(202) 408-4024

September 12, 2000

ATTORNEY DOCKET NO.: 04329.2392

Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

New U.S. Patent Application

Title: RECORDING AND REPRODUCING APPARATUS AND A METHOD
THEREOF

Inventors: Tadahiro Aihara and Takafumi Ito

Sir:

We enclose the following papers for filing in the United States Patent and Trademark Office in connection with the above patent application.

1. A check for \$1,180 representing a \$1140 filing fee and \$40 for recording the Assignment.
2. Application - 67 pages, including 6 independent claims and 32 claims total.
3. Drawings - 8 sheets of formal drawings containing 8 figures.
4. Declaration and Power of Attorney.
5. Recordation Form Cover Sheet and Assignment to Kabushiki Kaisha Toshiba .
6. Certified copy of Japanese Patent Application No. 11-373519 filed December 28, 1999.



TOKYO
011•813•3431•6943
BRUSSELS
011•322•646•0353

04329.2392

FINNEGAN, HENDERSON, FARABOW, GARRETT & DUNNER, L.L.P.
Assistant Commissioner for Patents
September 12, 2000
Page 2


Applicants claim the right to priority based on Japanese Patent Application No.11-373519 filed December 28, 1999.

Please accord this application a serial number and filing date and record and return the Assignment to the undersigned.

The Commissioner is hereby authorized to charge any additional filing fees due and any other fees due under 37 C.F.R. § 1.16 or § 1.17 during the pendency of this application to our Deposit Account No. 06-0916.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER, L.L.P.

By: 
Richard V. Burgujian
Reg. No. 31,744

RVB/FPD/cb
Enclosures

002760-06409960

TITLE OF THE INVENTION

RECORDING AND REPRODUCING APPARATUS AND A METHOD
THEREOF

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from the prior Japanese Patent
Application No.11-373519, filed December 28, 1999, the
entire content of which are incorporated herein by
reference.

10 BACKGROUND OF THE INVENTION

 This invention relates to a recording and
reproducing apparatus and to a method of recording and
reproducing contents.

 Most of the conventional portable audio players
15 which have a recording and reproducing function use
such medium as a magnetic tape, a magneto-optical disk
and others, and these players have a rotary drive
mechanism and accordingly have such problems as the
electric power consumption being relatively large, and
20 there being a limit to the miniaturization of the
device.

 In recent years, MP3 players have been developed
using an audio-compression technique of MPEG-1 audio
layer 3 which is capable of compressing the data amount
25 to 1/10 of an audio CD (compact disk) without
deteriorating the sound quality. Since the data can be
stored in a semiconductor memory, MP3 player is power

00260-06109260

saving and small. A light and compact portable audio player dealing with audio data for MP3, however, has a difficulty.

5 The difficulty occurs when the user tries to record new audio data in this portable audio player. It is necessary to connect the portable audio player with another device to reproduce content, and then to have the device start reproduction of a content and at the same time have the portable audio player start
10 recording of another content. It is more troublesome than expected.

Concretely, in order to store (record) audio data in a portable audio player, in addition to the portable audio player, a device to reproduce audio data, for
15 example, a CD player and others, is necessary. An output terminal of the device to reproduce audio data and an input terminal of the portable audio player are connected by means of a cable. When a digital signal is used, a cable for a digital signal such as an
20 optical cable is employed, whereas when an analog signal is used, a cable for an analog signal is used for connection.

Storage medium for recording content, such as a semiconductor memory card, are set in the portable
25 audio player, and the player stands ready for storage (recording).

The reproducing device prepares to reproduce

content, and when the reproducing device gets ready,
the storing (recording) operation of the portable audio
player is started, and then the reproduction operation
of audio data by means of the reproducing device is
5 carried out. Thus, the data is stored (recorded) in
the storage medium. When the recording is done by
means of a digital signal, it is possible to start the
storage (recording) automatically if only audio data is
reproduced.

10 In order to finish the storage, first the storage
of the portable audio player is completed, and then the
reproduction of the content reproducing device is
completed. When a digital signal is used for storage,
it is possible to complete the storage of the portable
15 audio player only by finishing the audio data
reproduction operation of the reproducing device.

In the above-described method, however, each time
new content is stored in the storage medium, it is
necessary to prepare both the content reproducing
20 device and the portable audio player.

When a personal computer is used as a content
reproducing device, it is possible for the personal
computer to control the start or stop of the recording
of the portable audio player, but it is not possible
25 for the portable audio player to control the personal
computer; accordingly, when the user records content in
the storage medium, the user needs to operate both the

content reproducing device and the portable audio player in time to each other.

Since the user needs to set up a number of operation steps to store content, such as the
5 connection of two devices by means of a cable, the reproduction and recording operations of respective devices, and others, it takes time and knowledge to operate the devices; therefore, only a limited number of users are capable of operating the devices.

10 Because the portable audio player with an insufficient CPU resource is not capable of executing a recording mode and a reproducing mode at the same time, the user needs to stop the reproduction to record audio data and to stop the recording to reproduce audio data.
15 Accordingly, the user cannot listen to songs which the user wants to in storing the content, and cannot store the data in listening to songs. It is inconvenient.

As described above, conventionally, in order to record new content from an audio data reproducing
20 device to a portable audio player, it is necessary to connect the two devices and operate the devices separately in time to each other. That is, it is necessary to execute the reproduction operation of the reproducing device, and to execute the recording
25 operation of the portable audio player. Thus, the conventional device needs a troublesome operation to record content; hence it is desirable to improve the

operationality.

In addition, in recording content such as audio, it was possible to listen to the content to be recorded by means of a monitor, but it was impossible to listen to audio data which the user wants to listen to other than the content being recorded because it was impossible to record or reproduce two contents at the same time.

BRIEF SUMMARY OF THE INVENTION

Accordingly, it is an object of the present invention to provide a recording and reproducing apparatus which is capable of reproducing a certain content and recording other content at the same time.

Another object of the present invention is to provide a recording and reproducing apparatus which is capable of recording a content without a complicated setting or operation.

According to the present invention, there is provided a recording and reproducing apparatus comprising means for recording a content supplied from an external device, means for reproducing the content, means for detecting that said reproducing means performs a reproduction when a recording command is issued, and means for disabling said reproducing means and enabling said recording means when said detecting means detects that said reproducing means performs the reproduction.

According to the present invention, there is provided another recording and reproducing apparatus comprising means for recording a content supplied from an external device, means for reproducing the content, 5 means for detecting that the apparatus is connected to the external device, means for setting an operation mode, and means for controlling said recording means and said reproducing means in accordance with the operation mode when said detecting means detects that 10 the apparatus is connected to the external device.

According to the present invention, there is provided a still another recording and reproducing apparatus comprising means for recording a content supplied from an external device, means for reproducing 15 the content, the reproducing means buffering content data before reproduction, means for detecting that a sufficient amount of the content data is buffered when a recording command is issued during reproduction, and means for enabling said recording means when said 20 detecting means detects that the sufficient amount of the content data is buffered.

According to the present invention, it is possible to record a content supplied from the external device without a complicated setting or operation.

25 Further, according to the present invention, it is possible to reproduce a content and record another content at the same time.

00560490-094300

Additional objects and advantages of the present invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the present invention.

The objects and advantages of the present invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the present invention and, together with the general description given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the present invention in which:

FIG. 1 is a diagram showing the entire system of a first embodiment according to the present invention;

FIG. 2 is a flow chart explaining the first embodiment according to the present invention;

FIG. 3 is a flow chart explaining a second embodiment according to the present invention;

FIG. 4 is a flow chart explaining a third embodiment according to the present invention;

FIG. 5 is a flow chart explaining a fourth embodiment according to the present invention;

FIG. 6 is a flow chart explaining a fifth embodiment according to the present invention;

FIG. 7 is a flow chart explaining the fifth embodiment according to the present invention; and

5 FIG. 8 is a flow chart explaining a sixth embodiment according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

A preferred embodiment of a recording and reproducing apparatus and method according to the present invention will now be described with reference to the accompanying drawings.

First Embodiment

FIG. 1 is a block diagram of a portable audio player (a player hereinafter) as an embodiment of a recording and reproducing apparatus according to the present invention. The player 1 comprises a CPU (processor) 2 which is a center of operations and control; a ROM 3 which is a read-only memory to store programs and others; a RAM 4 which is a random-access memory used for storing data temporarily and executing programs; a medium I/F 5 which is an interface with which such devices as a memory card are connected and which thereby transmits and receives a content; a peripheral I/F 6 which is an interface connected with the content reproducing device by a standard connector such as an USB (Universal Serial Bus) connector and transmitting and receiving data in bi-directional

15

20

25

The user I/F 8 is connected with a plurality of button switches 8a formed in the main body of the player 1. Among these switches 8a, there are a volume

switch for adjusting the volume, reproduction and stop switches giving commands to reproduce or stop reproduction, forward and backward skip switches, a power switch for the ON/OFF operation of the power source, and a recording switch for recording the content. The user I/F 8 is an interface for giving the CPU 2 the information to the effect that the above switches are operated.

The portable audio player according to the first embodiment is configured in such a way that only by pressing the recording switch of the player, when the player is reproducing the content, the player can automatically stop reproduction and start recording of the content given by the personal computer 12, or irrespective of whether the player is not operating or whether the power is off, the player can automatically record the content from the personal computer 12.

The peripheral I/F 6 employs an USB interface which can transmit data in bi-direction manner, one of the standard connecting interfaces of the personal computer 12.

The medium I/F 5 is an interface which reads out data from or writes data in the memory card 11. The memory card 11 stores compressed audio content in PCM (Pulse Coded Modulation) form, ADPCM (Adapted PCM) form or MP3 (MPEG-Audio Layer 3) form, MPEG-2 AAC (Advanced Audio Coding) form and others; when the content from

the personal computer 12 via the peripheral I/F 6 is recorded in the memory card 11, the above-mentioned audio content in a file form is output via the USB cable 14, the peripheral I/F 6 and can be stored in the memory card 12 as a file.

The audio I/F 7 comprises a D/A converter which converts a digital signal into an analog signal, an amplifier which amplifies an analog signal obtained after the conversion by the D/A converter, and a terminal (output terminal) which outputs an analog signal amplified by the amplifier to the outside, and the user can hear the reproduced sound by connecting the earphone (or headphone) 13 to the output terminal and thereby converting an analog signal into sound.

The memory card 11 can be fitted on or removed from the player 1 freely, and when the memory card 11 is fitted on the player 1, if the user operates the reproducing switch, the CPU 2 accordingly executes the program in the ROM 3 so that the content recorded in the memory card 11 may be converted into a predetermined data form, and output to the earphone 13 via the audio I/F 7.

The display device 10 displays the results of a given operation, and others.

The personal computer 12 connected to the player 1 is supposed to have the content to be recorded in the player 1 and a transmission program thereof.

That is, the content is stored in the personal computer 12, which is provided with a program for transmitting the stored content; this transmission program functions in such a way that when executed, the
5 program prepares to transmit the content specified by the user, uses a built-in external I/F with the USB connector to transmit data to or receive data from the player 1, and when the program receives a content request signal from the player 1 via the built-in
10 external I/F, after outputting a content output notification, the program begins to transmit the content specified by the user. The personal computer 12 also has a function of transmitting an end-of-content notification to the player 1 when the whole
15 content is transmitted.

The operation of the player 1 according to the first embodiment configured as described above is described with reference to an operation flow chart shown in FIG. 2. The player 1 according to the first
20 embodiment is characterized in that the content can be recorded with a single operation under any conditions.

In order to record the content, the player 1 is connected with the personal computer 12 through the peripheral I/F 6 by means of the USB cable 14.
25 Naturally, the personal computer 12 has the content to be recorded and the transmission program of the content. When the user makes the personal computer 12 execute

the transmission program of the content and specifies the content and then gives an command to execute the transmission, the personal computer 12 prepares to transmit the content, functions so that the content may be transmitted to and received from the player 1 using the built-in external I/F with the USB connector, and waits for the content request signal from the player 1 through the external I/F.

In the player 1, the CPU 2 which executes the programs determines whether or not if a recording button is depressed in step S51. If the recording button is depressed, the CPU 2 determines the current status of the player 1 at that time (step S52).

If the determination shows that the player 1 is reproducing content, the CPU 2 makes the player 1 stop reproduction (step S53). The CPU 2 proceeds to step S54. If the determination in step S52 shows that the power is on but that the player 1 is stopped, the CPU 2 directly proceeds to step S54. If the determination in step S52 shows that the power is off, the CPU 2 proceeds to step S55, and controls the power source so that the power is on, and thereafter proceeds to step S54.

In step S54, the CPU 2 output a content request signal to the personal computer 12 via the peripheral I/F 6. On receiving the content request signal, the personal computer 12 outputs a content output

notification (step S55), while the player 1, on receiving the output notification, starts recording of content in the memory card 11 (step S57).

As described above, the content is stored in the personal computer 12, which is provided with a program for transmitting the stored content; this transmission program functions in such a way that when executed, the program prepares to transmit the content specified by the user, uses the external I/F with the USB connector to transmit data to or receive data from the portable audio player 1, and when the program receives the content request signal from the player 1 via the external I/F, after outputting a content output notification, the program begins to transmit the content specified by the user.

Accordingly, after the player 1 outputs the content request signal in step S54, the personal computer 12, after outputting the content output notification, starts to transmit the content specified by the user.

In the player 1, the CPU 2, after receiving the content output notification from the personal computer 12 (step S56), receives the content transmitted from the personal computer 12 through the peripheral I/F 6, and records the content in the memory card 11 through the medium I/F 5 (step S57).

When the transmission of the content to be

external device and by operating the recording operation switch, the recording of the received content in the storage medium gets ready; therefore it is possible to record a variety of content such as audio and visual data from the external device in the storage medium easily without complicated operations.

It may be possible to modify the first embodiment such that the stopped reproduction (at step S53) is automatically restarted after the recording is completed (step S59).

Other embodiments of the recording and reproducing apparatus and method according to the present invention will be described. The same portions as those of the first embodiment will be indicated in the same reference numerals and their detailed description will be omitted.

Second Embodiment

In the above embodiment, it is possible to record content easily in the storage medium with one touch of the recording switch of the player 1 without operating the external device as content reproducing device and the player 1 as recording device in time to each other, and accordingly it is possible to stop the reproduction automatically even when the content is reproduced so that the content may be recorded.

The second embodiment of recording and reproducing apparatus will be described below which is capable of

recording content other than content being reproduced and reproducing the content without interrupting, and of recording and reproducing the contents at the same time.

5 The basic constitution of the player 1 in the second embodiment is as shown in FIG. 1, and all the components have the same function as that of the components described in the first embodiment except the program of the ROM 3 and the user I/F 8; therefore only
10 different components will be described here.

 In the second embodiment, so that it may be possible to record and reproduce different contents at the same time, the program of the ROM 3 is capable of executing the recording operation and the reproducing
15 operation simultaneously. When the content is reproduced, content is spooled in the memory (RAM 4) and then the reproducing is started, thereby it is possible to reproduce the content without interruption when the received content is recorded. For that
20 purpose, the ROM 3 is programmed in such a way that it is possible to record and reproduce the contents simultaneously and to starting reproduction after a sufficient amount of data (more than the required amount preset so that the content may be reproduced
25 without interruption) is spooled in the RAM 4.

 Therefore, the received content can be recorded while another content is reproduced. Since the recording of

the content transmitted from the personal computer 12 is started when the personal computer 12 transmits a recording command, the personal computer 12 is programmed to transmit the recording command before
5 transmitting the content to the player 1 which records the content. When the personal computer 12 receives a standby command from the player 1, the personal computer 12 waits for executing the transmission of the content until the standby command is cancelled; when
10 the standby command is cancelled, that is, when the personal computer 12 receives a data output permission notification from the player 1, the personal computer 12 starts transmission of the content.

Accordingly, in the player 1, the program of the
15 ROM 3 is configured such that when the player 1 is ready to reproduce the content, if the amount of the spooled data to be reproduced is not enough, the player 1 transmits the standby command to the personal computer 12 through the peripheral I/F 6 until a
20 sufficient amount of the spooled data (at least the above-mentioned required amount, or more) is detected; and when the spool of the content is completed, the player 1 outputs the data output permission notification.

25 The personal computer 12 has a function of transmitting an end-of-content notification to the player 1 when the transmission of the content is

00550490-094900

completed.

The operation of the player 1 according to the second embodiment configured as described above will be described below with reference to an operation flow chart shown in FIG. 3.

The personal computer 12 connected to the player 1 stores the content to be recorded in the player 1 and the transmission program thereof.

That is, the content is stored in the personal computer 12, which is provided with a program for transmitting the stored content; this transmission program functions in such a way that when executed, the program prepares to transmit the content specified by the user, uses the built-in external I/F with the USB connector to transmit data to or receive data from the player 1, and when the program receives a content request signal from the player 1 via the built-in external I/F, after outputting a content output notification, the program begins to transmit the content specified by the user.

The player 1 and the personal computer 12 are connected through the peripheral I/F 6 by means of the USB cable 14.

The user operates the personal computer 12 having the content to be recorded and the transmission program of the content to execute the transmission program of the content, and gives an command to execute the

transmission after specifying the content.

The personal computer 12 prepares to transmit the content, functions so as to transmit data to or receive data from the player 1 through the built-in external I/F using the USB connector and thereby transmit a recording command to the player 1 through the built-in external I/F. The personal computer 12 waits for a data output permission notification from the player 1.

In the player 1, on the other hand, the CPU 2 executing the program of the ROM 3 performs the process as follows. When the CPU 2 starts to execute the program (step S90), the CPU 2 first determines whether or not the CPU 2 is recording a content or whether or not a recording command is supplied from the personal computer 12 or the user I/F 8 (button switches 8a) (step S91). If the CPU 2 determines that a content is being recorded or there is the recording command, the CPU 2 proceeds to step S100.

In step S91, if the CPU 2 determines that there is no recording command or a content is not being recorded, then the CPU 2 determines whether or not the CPU 2 is reproducing a content or whether or not there is a reproduction command supplied from the user I/F 8 or from the personal computer 12 (step S92). If the CPU 2 determines that it is not the case in step S92, the CPU 2 returns to step S91; if the CPU 2 is reproducing a content or there is the reproduction command, the CPU 2

In step S91, if the CPU 2 determines that a
5 content is being recorded or there is the recording
command, the CPU 2 proceeds to step S100, where the CPU
2 determines whether or not the CPU 2 is reproducing a
content or whether there is the reproduction command.
If the CPU 2 determines that neither is the case in
10 step S100, the CPU 2 proceeds to step S105.

If there is not a sufficient amount of spooled data, the CPU 2 outputs a data output standby command to the personal computer 12 (step S102), reads the data from the memory card 11 (step S103), and spools the data in the memory (RAM 4) (step S104). The reproduction is continued all the while.

The personal computer 12, on receiving the data output standby command, waits for the transmission of a content until the standby command is cancelled. Thus, 25 the player 1 can be devoted to reproduction, and the data required to make it possible for the content to be reproduced without interruption can be spooled in the

reproduced, the player 1 temporarily stops the
receiving of the content to be recorded to give the
reproduction priority, and therefore the recording can
be performed automatically only by a command from the
5 personal computer 12.

As described above, the recording and reproducing
apparatus according to the second embodiment comprises
the interface for being connected with the external
device which is capable of bi-directional communication,
10 the storage medium capable of recording and reproducing
the content such as audio and visual data, and the
spool memory (RAM 4) to spool the data to be reproduced.
The recording and reproducing apparatus determines the
status thereof on receiving a content recording command
15 from the external device, and when a content is being
reproduced, if a sufficient amount of the data to be
reproduced is spooled in the spool memory, permits the
receiving of the content and has the content received
through the interface recorded in the storage medium.
20 If there is not a sufficient amount of the spooled data,
the receiving of the content is suspended until there
is a sufficient amount of the spooled data, and the
receiving of the content is permitted after there is a
sufficient amount of the spooled data, then, the
25 content received is recorded in the storage medium.

As is described above, the player 1 in this
embodiment reproduces the content after the content is

spooled in the spool memory (RAM 4). When the player 1 receives a content recording command from the personal computer 12, the player 1 determines the status thereof. When a content is being reproduced, if there is a
5 sufficient amount of the spooled data to be reproduced, the receiving of the content is permitted, and the content received through the interface from the external device is recorded in the storage medium. If there is not enough amount of the spooled data, the
10 receiving of the content is permitted after there is enough amount of the spooled data, and then, the received content is recorded in the storage medium.

Accordingly, it is possible to reproduce content such as audio and visual data without interruption and
15 to perform recording simultaneously and automatically. There can be provided a portable audio player capable of recording and reproducing simultaneously which is extremely easy to handle.

Third Embodiment

20 In the above embodiments, it is possible to record and reproduce the contents simultaneously. The third embodiment will be described below which is capable of stopping the reproduction and recording the content automatically, or recording the content automatically
25 after the completion of the reproduction according to the operation mode set up in the player 1 upon being connected by means of a cable to the personal computer

12 which provides the content.

In this embodiment too, the basic constitution of the player 1 is as shown in FIG. 1, and all the components have the same function as that of the components described in the first embodiment except the program of the ROM 3 and the user I/F 8. Accordingly, only different components will be described here.

In a portable audio player in the third embodiment is provided with a plug and play function of automatically detecting and recognizing the connection with the external device and enabling the use thereof, which recent personal computers have. This function enables the program in the ROM 3 to prepare to start the communication when the personal computer 12 and the player 1 are connected by means of a bi-directional communication cable, for instance, the USB cable 14, and thereafter to start the execution.

The user I/F 8 is connected to a plurality of switches formed in the main body of the player 1. Among these switches, there is a volume switch, a reproduction and stop switch, forward and backward skip switches, a power switch, a switch for recording in the memory card 11, and a mode setting switch to set up the operation mode of the reproduction and recording of the content.

The mode setting switch is capable of selecting one of the following four modes and performing the

program performs an operation according to the content of the setting by reading the set up information in the flash memory 9.

5 The operation of the player 1 according to the third embodiment configured as described above will be described below with reference to an operation flow chart shown in FIG. 4.

10 The personal computer 12 connected to the player 1 stores the content to be recorded in the player 1 and the transmission program thereof.

15 That is, the content is stored in the personal computer 12, which is provided with the program for transmitting the stored content; this transmission program functions in such a way that when executed, the program prepares to transmit the content specified by the user, using the external I/F with the USB connector to transmit data to or receive data from the player 1. When the program receives a content request signal from the player 1 via the external I/F, after outputting a content output notification, the program starts to
20 transmit the content specified by the user.

25 The user operates the personal computer 12 having the content to be recorded and the transmission program of the content to execute the content transmission program, and the user gives an command to execute the transmission after specifying the content.

 The player 1 and the personal computer 12 are

connected by means of the USB cable 14.

The personal computer 12 prepares to transmit the content, functions so as to transmit data to and receive data from the player 1 through the external I/F using the USB connector, and thereby transmits a recording command to the player 1 through the external I/F. The personal computer 12 waits for a data output permission notification from the player 1.

In the player 1, on the other hand, the CPU 2, by executing the program in the ROM 3, executes the process as in a flow chart in FIG. 4

The CPU 2 of the player 1 which is executing the program, when the cable 14 is connected (step S1), determines whether or not the content is being reproduced (step S2). If the CPU 2 determines that the content is being reproduced, the CPU 2 sets the status flag at "1" (step S3a), and then reads the setting content of the operation mode from the flash memory 9 and based on the information determines the operation mode (step S4).

If the CPU 2 determines that the content is not being reproduced in step S2, the CPU 2 sets the status flag at "0" in step S3b and proceeds to step S4. If the set mode is the reproduction priority mode in step S4, the CPU 2 proceeds to step S11, where the CPU 2 determines whether or not the status flag is "1". If the status flag is determined "1", the CPU 2 changes

5 If the status flag is determined "0" in step S11,
the CPU 2 determines that the player 1 is stopped or
the power is off, and proceeds to step S22.

20 If the operation mode is the post-recording
reproduction mode, and the status flag is "1", the CPU
2 restarts the reproduction (step S27).

In step S4, if the CPU 2 determines that the set mode is the recording priority mode or the post-recording reproduction mode, the CPU 2 proceeds to step S21 and stops the reproduction. In step S22, the CPU 2 transmits a recording permission notification to the

personal computer 12. The personal computer 12 accordingly transmits the content to be recorded, which the CPU 2 records in the memory card 11 (step S23). When the whole content is transmitted, the personal computer 12 transmits an end-of-content notification (step S24), and accordingly the recording is stopped (step S25).

In step S26, the CPU 2 determines the operation mode and the status flag, and if the status flag is determined "1" and the operation mode is determined the post-recording reproduction mode, in step S27, the CPU 2 restarts reproduction of the content, while if the status flag is determined "0" or the operation mode is determined the recording priority mode or the post-reproduction recording mode, the CPU 2 stops in step S28.

In step S4, if the mode setting is determined the post-reproduction recording mode, then the CPU 2 determines whether or not the status flag is "1" (step S31). If the flag is "1", the CPU 2 determines that a cable is connected during the reproduction of the content, and changes the status flag back to "0" (step S32) and transmits a recording inhibition notification to the personal computer 12 (step S33).

25 The personal computer 12, on receiving the
recording inhibition notification from the player 1,
waits until a recording permission notification is

transmitted from the player 1. The player 1 continues the reproduction of the content, and when the reproduction of the content is completed (step S34), the CPU 2 outputs a recording permission notification
5 to the personal computer 12 (step S22).

Thereafter, the CPU 2 executes the same processes and operations as steps S23 to S28 in the case of the recording priority mode.

If the status flag is "0" in step S31, the CPU 2
10 determines that the content is not reproduced when the USB cable 14 is connected, and proceeds to step S22. Thereafter, the same processes and operations as steps S23 to S28 in the case of the recording priority mode are executed.

15 As described above, it is possible to provide a portable audio player capable of stopping the reproduction and recording the content automatically, or of recording the content automatically after the reproduction is completed, according to the preset
20 operation mode by connecting the player with the personal computer 12 which provides the content.

The recording and reproducing apparatus in the third embodiment comprises the interface for being connected with the external device by means of a bi-
25 directional communication cable, and the storage medium capable of recording and reproducing the content such as audio and visual data. The recording and

By making it possible to set the relation between the reproduction and the recording in a variety of ways, it is possible to provide a portable audio player which is capable of selecting from a variety of forms such as automatically recording the content transmitted from a content provider, for example, a personal computer, automatically recording the content after the completion of the reproduction of the content, or interrupting the reproduction of the content and after automatically recording the content, resuming the reproduction of the content the reproduction of which has been interrupted, and which is capable of automatically executing the operations of reproduction or recording easily only by means of the connection with a bi-directional communication cable.

Fourth Embodiment

Now the fourth embodiment will be described which is capable of controlling the reproduction and recording of the content on the part of the player by the operation of only the external device.

A portable audio player in the fourth embodiment according to the present invention will be described. The player 1 capable of automatically reproducing and recording content by the operation of only the external device. In this embodiment too, the basic constitution of the player 1 is as shown in FIG. 1, and all the components have the same function as that of the

command.

The operation of the player 1 will be described below with reference to the operation flow chart in FIG. 5.

5 In the fourth embodiment, the personal computer 12 having the content to be recorded and the transmission program thereof and the player 1 are connected by means of the USB cable 14. Under this condition, the player 1 always receives a command signal from the personal
10 computer 12 (step S70).

 The user operates the personal computer 12 to execute the player operating program. In order to record the content, the user specifies the content and gives a command to start recording, while in order to
15 reproduce the content, the user gives a command to start reproduction. In the former case, the personal computer 12 transmits a recording command signal as a command signal, and in the latter case, the personal
20 computer 12 transmits a reproduction command signal as a command signal.

 In the player 1 standing by for the reception of a command signal from the personal computer 12, the CPU 2 determines what the received command is. If the received command is a recording or reproduction command,
25 the CPU 2 stores the contents of the received command in the RAM 4 (step S71). The CPU 2 determines the current status of the player 1 (step S72). In step S72,

the CPU 2 determines whether or not the power is on or off, whether the content is reproduced or recorded or the process is stopped.

After the determination of the current status of the player 1 in step S72, if the content is being reproduced, the CPU 2 determines the contents of command stored in step S71 (step S73). If the command stored in step S71 is the reproduction command, the CPU 2 has the reproduction of the content continued (step S78), while if the command stored in step S71 is the recording command, the CPU 2 has the reproduction stopped (step S76), and then proceeds to step S79.

As a result of the determination (determination of the current status of the player 1) in step S72, if the power is on but the reproduction is stopped, the CPU 2 determines the command stored in step S71 (step S74). If the command is determined to be the reproduction command, the CPU 2 starts the reproduction of the content (step S78). If the command is determined to be the recording command in step S74, the CPU 2 proceeds to step S79.

If the CPU 2 determines that the power is off in step S72, the CPU 2 turns the power on (step S75), and determines the command in step S71 (step S77). If the command is determined to be the reproduction command, the content is reproduced (step S78), and if the command is determined to be the recording command, the

CPU 2 proceeds to step S79.

In step S79, the CPU 2 transmits a content request signal to the personal computer 12 through the peripheral I/F 6. The personal computer 12, on receiving the content request signal, transmits a content output notification, while the player 1, on receiving the notification (step S80), starts to record the content in the memory card 11 (step S81).

That is, as described above, the content is stored in the personal computer 12, which stores the program for transmitting the stored content. The transmission program functions in such a way that when executed, the program prepares to transmit the content specified by the user, and uses the USB connector to transmit data to or receive data from the player 1. When the program receives a content request signal from the player 1 via the built-in external I/F, after outputting a content output notification, the program starts to transmit the content specified by the user.

Accordingly, the player 1 outputs the content request signal in step S79, and the personal computer 12, on receiving the content request signal, outputs a content output notification, and starts to transmit the content specified by the user.

In the player 1, the CPU 2, after receiving the output notification from the personal computer 12, receives the content transmitted from the personal

computer 12 through the peripheral I/F 6, and records the content in the memory card 11 through the medium I/F 5 (step S81).

When the transmission of the content is completed, the personal computer 12 transmits an end-of-content notification. The CPU 2 of the player 1 receives the notification. The player 1 receives the content end-of-content notification in step S82 and after the completion of the recording in step S83, the player 1 returns to step S70 and waits for the receiving of the command signal from the personal computer 12.

As described above, in this embodiment when the player is connected with external device such as a personal computer, the player gets ready to receive a command signal from the external device. When the external device transmits a reproducing or recording command signal, the player reproduces or records the content according to the command signal. Thus, it is possible to make the portable audio player automatically reproduce or record the content with the operation of only the external device without directly operating the portable audio player.

The recording and reproducing apparatus in this embodiment comprises the interface which is capable of bi-directional communication for being connected with an external device, the storage medium capable of recording and reproducing the content such as audio and

5 communication cable, and the recording or reproducing is executed according to the recording or reproducing command signal given by the external device. After the completion of the recording or reproducing, a command signal from the external device is again waited for.

15 Fifth Embodiment

In the second embodiment, when different contents are recorded and reproduced simultaneously, if a sufficient amount of the reproduced data is not spooled, in order to give priority to the reproduction, the receiving of the recorded data is stopped temporarily until a sufficient amount of the reproduced data is spooled. However, there may occur a case in which the recording cannot be started forever. The fifth embodiment will now be described which is capable of automatically reproducing or recording the content successively according to a preset operation mode when the process load is too heavy for the simultaneous

execution of recording and reproduction.

The basic constitution of the player 1 in this embodiment is as shown in FIG. 1, and all the components have the same function as that of the components described in the first embodiment except the program of the ROM 3 and the user I/F 8. Accordingly, only different components will be described here.

In the fifth embodiment, the user I/F 8 is connected with a plurality of switches formed in the main body of the player 1. These switches are a volume switch, a reproduction and stop switch, forward and backward skip switches, a power switch, and a mode setting switch for setting up the operation mode. A program is stored in the ROM 3 which is capable of recording and reproducing different contents simultaneously and which determines the load of the CPU and when the load is too heavy for the simultaneous execution of recording and reproducing, is capable of automatically reproducing or recording the content according to the preset mode. This mode is not only set by a command of the player 1, but by a command from the personal computer 12. When the content is reproduced, the reproduced content is spooled in the memory (RAM 4) before the reproduction is started, which makes it possible to reproduce the content without interruption while a received content is recorded. For that purpose, the program in the ROM 3

is programmed so as to be capable not only of recording and reproducing the data simultaneously but of spooling a sufficient amount in the RAM 4 before starting the reproduction so that the content may be reproduced without interruption, and of recording the received content at any time during the reproduction. The recording of the content received from the personal computer 12 is started when a recording command is transmitted from the personal computer 12; accordingly, the personal computer 12 transmits a recording command to the player 1 before transmitting the content to the player 1 for the recording.

The personal computer 12 has a function of suspending the transmission of the content until a standby command is cancelled in receiving a data output standby command from the player 1, and when a standby command is cancelled, that is, when the personal computer 12 receives a data output permission notification from the player 1, the personal computer 12 starts transmitting the content.

Accordingly, the player 1 has a program in the ROM 3 which transmits to the player 1 through the I/F 6 a notification to the effect that the data output should be suspended until a sufficient amount of reproduced data is spooled in the memory when the player 1 is ready to reproduce the content but there is not enough spool amount of the reproduced data, and which outputs

a data output permission notification when the sufficient spool of the content is completed.

The personal computer 12 also has a function of transmitting the content specified by the user by means of a bi-directional communication cable, and a function of transmitting an end-of-content notification to the player 1 when the transmission of the content is completed.

The operation of the player 1 in the fifth embodiment configured as described above will be described now with reference to operation flow charts in FIGS. 6 and 7. The flow chart in FIG. 6 shows the process of measuring the CPU load, spooling the reproduced data and recording the content at the time of the recording and reproduction. The flow chart in FIG. 7 shows the process carried out when the CPU load is too heavy for the simultaneous execution of the recording and reproduction.

The personal computer 12 connected to the player 1 is provided with the content to be recorded in the player 1 and a transmission program thereof.

That is, the content is stored in the personal computer 12, which is provided with the program for transmitting the stored content. The transmission program functions in such a way that when executed, the program prepares to transmit the content specified by the user, and uses the built-in external I/F with the

USB connector to transmit data to or receive data from
the player 1. When the program receives a content
request signal from the player 1 via the built-in
external I/F, after outputting a content output
5 notification, the program starts to transmit the
content specified by the user.

The player 1 and the personal computer 12 are
connected through the peripheral I/F 6 by means of the
USB cable 14.

10 The user operates the personal computer 12 having
the content to be recorded and the transmission program
of the content to execute the transmission program of
the content, and the user gives a command to execute
the transmission after specifying the content.

15 The personal computer 12 prepares to transmit the
content, functions so as to transmit data to and
receive data from the player 1 through the built-in
external I/F having the USB connector and thereby
transmit the recording command to the player 1 through
20 the built-in external I/F. The personal computer 12
stands by for a data output permission notification
from the player 1.

In the player 1, on the other hand, the CPU 2
executes the process by carrying out the program in the
25 ROM 3. When the program is started (step S120), the
CPU 2 first determines whether or not the CPU 2 is
recording the content or a recording command is output

from the personal computer 12 or the user I/F 8 (step S121). If the CPU 2 determines that the CPU 2 is recording the content or there is the recording command, the CPU 2 proceeds to step S130.

5 In step S121, if the CPU 2 determines that there is no recording command or that the CPU 2 is not recording the content, the CPU 2 proceeds to step S122, and determines whether or not the CPU 2 is reproducing the content or there is a reproduction command output
10 from the user I/F 8 or the personal computer 12. In step S122, if the CPU 2 determines that the CPU 2 is not reproducing the content or there is no reproduction command, the CPU 2 returns to step S121, while if the CPU 2 is reproducing the content or there is the
15 reproduction command, the CPU 2 reads the data from the memory card 11 storing the content (step S123), spools the data in the memory (RAM 4), and reproduces the content (step S124).

 In step S121, if the CPU 2 determines that the
20 CPU 2 is recording the content or there is the recording command, the CPU 2 proceeds to step S130, in which the CPU 2 determines whether or not the CPU 2 is reproducing the content or there is the reproduction command. If neither is the case in step S130, the
25 CPU 2 proceeds to step S151.

 On the other hand, if the CPU 2 determines that the CPU 2 is reproducing the content or there is the

reproduction command in step S130, the CPU 2 proceeds to step S131 and calculates the current load of the CPU 2. If it is determined that the load will allow the simultaneous execution of the recording and reproduction, the CPU 2 proceeds to step S132.

In step S132, the CPU 2 determines whether or not there is enough amount of the reproduction data spooled in the memory (RAM 4). If there is not enough amount of the spooled data, the CPU 2 outputs a data output standby command to the personal computer 12 (step S133), reads the data from the memory card 11 (step S134), and spools the data in the memory (RAM 4) (step S135).

The personal computer 12, on receiving the data output standby command, suspends the transmission of the content until the standby command is cancelled.

As described above, the CPU 2 reads and spools the data until enough amount of data is spooled in the memory so that the content may be reproduced without interruption when the operation of reading the data from the personal computer 12 is executed.

When there is a sufficient amount of data spooled in the memory, the CPU 2 outputs a data output permission notification to the personal computer 12 (step S151). On receiving the notification, the personal computer 12 outputs the content as packet data, which the player 1 receives (step S152).

After receiving the packet data, the CPU 2

5

10

15

25

in step S161, and the specified content is reproduced (or the reproduction is continued) in step S162. If there remains no content to be reproduced, the reproduction is completed (step S163), and the CPU 2
5 returns to the process in step S121.

In the recording priority mode, the CPU 2 outputs a notification to the effect that the reproduction is not permitted to the display device 10 in step S170. The CPU 2 has the display device 10 indicate that the
10 reproduction is inhibited. The CPU 2 outputs a recording permission notification to the personal computer 12 (step S171), and receives the packet data transmitted (step S172). The CPU 2 determines whether or not there is an end-of-content notification
15 transmitted from the personal computer 12 (step S173), and if the recording is not completed, the CPU 2 transmits a data standby command to the personal computer 12 (step S174), and after recording the data received in step S175 in the memory card 11, outputs a
20 recording permission notification again to the personal computer 12 (step S171).

If the CPU 2 receives an end-of-content notification from the personal computer 12 in step S173, the CPU 2 proceeds to step S184 in which the received
25 data is recorded in the memory card 11, and completes the recording (step S177). The CPU 2 determines the operation mode (step S178), and if the operation mode

is the post-recording reproduction mode, the CPU 2 restarts the interrupted reproduction (step S179), and returns to step S121.

As a result of the determination in step S178, if
5 the operation mode is the recording priority mode, the CPU 2 returns to step S122 without doing anything.

As a result of the operation mode determination in
step S160, if the operation mode is the post-
reproduction recording mode, the CPU 2 proceeds to the
10 process in step S180, where the CPU 2 outputs a
recording inhibition notification to the personal
computer 12. The CPU 2 reproduces the content or
continues the reproduction (step S186), and when there
remains no content to be reproduced, the CPU 2
15 completes the reproduction (step S176), and proceeds to
step S171.

As a result of the operation mode determination in
step S160, if the operation mode is the post-recording
reproduction mode, the CPU 2 proceeds to step S181,
20 where the CPU 2 has the reproduction suspended, and
proceeds to step S171 and executes the processes of
step S171 and the subsequent steps described above.

Thus, by selecting from modes such as the
reproduction priority mode which gives priority to the
25 reproduction, the recording priority mode which gives
priority to the recording, the post-reproduction
recording mode which starts the recording after the

reproduction if the content is reproduced, and the post-recording reproduction mode which interrupts the reproduction if the content is reproduced and carries out the recording and then restarts the reproduction after the completion of the recording, and by carrying out control according to the selected mode, it is possible for a player incapable of recording and reproducing different contents simultaneously to automatically reproduce or record the content.

10 The recording and reproducing apparatus according to the fifth embodiment comprises the interface which is capable of bi-directional communication and is connected with the external device providing the content, the storage medium capable of recording and reproducing the content such as audio and visual data, 15 the mode setting means which sets up mode information to specify which of the reproduction and the recording is given priority, and the control means which gives priority to either the reproduction or the recording according to the preset mode when the recording of the 20 content transmitted from the external device and the reproduction of the content compete and the simultaneous execution of the recording and reproduction is impossible because of the limitation of 25 the process capability of the CPU.

When the recording and the reproduction compete and both cannot be executed simultaneously, either the

00560490-004500

recording or the reproduction is selected automatically according to the preset mode, and the process with low priority is interrupted and restarted later. Thus, it is possible to carry out the recording and reproduction as desired with a simple operation. Manual operations to interrupt the reproduction when the recording is carried out, or to interrupt the recording when the reproduction is carried out are not necessary.

Therefore, the recording and reproduction is executed with an extremely simple operation.

Sixth embodiment

In the fifth embodiment, when the load of the CPU is too heavy for the simultaneous execution of the recording and reproducing, either the recording or the reproduction is suspended according to the operation mode preset in the player 1. Now, the sixth embodiment will be described which is capable of automatically executing the reproduction or recording of the content successively according to a command from the external device.

A player 1 according to this embodiment is capable of being remotely controlled its reproduction and recording of the content by the operation of only the external device connected with the player 1 by means of a bi-directional communication cable. Basic constitution of the player 1 in this embodiment is as shown in FIG. 1, and all the components have the same

function as that of the components described in the first embodiment except the program of the ROM 3. Accordingly, only different components will be described here.

5 In the sixth embodiment, a program in the ROM 3 is capable of the operations of recording and reproducing the content simultaneously so that different contents may be recorded and reproduced simultaneously by the CPU 2. When the content is reproduced, the reproduced
10 content is spooled in the memory (RAM 4) before the reproduction is started, which makes it possible for the reproduced content to be reproduced without interruption when received content is recorded. For that purpose, the program in the ROM 3 is capable not
15 only of recording and reproducing the data simultaneously but of spooling a sufficient amount of data in the RAM 4 before starting the reproduction so that the reproduced content may be reproduced without interruption and of recording the received content at
20 any time during the reproduction. The recording of the content received from the personal computer 12 is started when a recording command is transmitted from the personal computer 12. Accordingly, the personal computer 12 transmits a recording command to the player
25 1 before transmitting the content to the player 1 for the recording. The personal computer 12 has a function of suspending the transmission of the content until a

standby command is cancelled in receiving a data output
standby command from the player 1. When the standby
command is cancelled, that is, when the personal
computer 12 receives a data output permission
5 notification from the player 1, the personal computer
12 starts transmitting the content.

Accordingly, the player 1 has a program in the ROM
3 which transmits to the external device through the
I/F 6 a notification to the effect that the data output
10 should be suspended until there is enough amount of the
spooled data when the player 1 is ready to reproduce
the content but there is not enough amount of the
spooled data, and which outputs a data output
permission notification when the spool of the content
15 is completed.

The personal computer 12 has a function of
transmitting an end-of-content notification to the
player 1 when the transmission of the content is
completed, and also has a function of indicating which
20 of the reproduction and the recording is given priority
on receiving a command request signal requiring the
indication of the reproduction or recording transmitted
by the player 1. The selection of the indication may
be manually specified by the user or may be done by the
25 program.

The personal computer 12 also has a function of
suspending the transmission of the content to the

player 1 on receiving a recording inhibition notification from the player 1, a function of suspending the transmission of the content currently being transmitted on receiving a data output standby command, and others. The function of suspending the data output makes the transmitting side suspend the transmission until the receiving side completes the process of recording the data accumulated in a receiving buffer in the memory card 11. In order to make good use of this function, this embodiment employs the packet transmission in which the content is transmitted by the packet.

The operation of the player 1 in the sixth embodiment configured as described above will be described with reference to the operation flow charts shown in FIGS. 6 and 8. The flow chart in FIG. 6 shows the process of measuring the CPU load, spooling the reproduced data and recording the content at the time of the recording and reproduction, and this process is the same as in the fifth embodiment. The operation flow chart in FIG. 8 shows a process carried out when the load is too heavy as a result of the load measurement for the simultaneous execution of the recording and reproduction.

As a result of the CPU load calculation in step S131, if the load is such that the recording and the reproduction cannot be carried out simultaneously, the

CPU 2 proceeds to step S200 in FIG. 8.

The CPU 2 outputs a command request signal to the personal computer 12 in step S200, having the personal computer 12 select whether to carry out the reproduction or the recording. The personal computer 12 accordingly displays a screen requiring the indication of the selection of either the reproduction or the recording. The user, on receiving this requirement, gives a command of either the reproduction or the recording.

The player 1 receives the command after the personal computer 12 transmits the command of either the reproduction or the recording, and the CPU 2 determines the command transmitted from the personal computer 12 (step S201).

If the CPU 2 determines that the command is the reproduction command, the CPU 2 outputs a recording inhibition notification to the personal computer 12 (step S202). The CPU 2 continues or starts the reproduction (step S203), and when the reproduction process of the content to be reproduced is completed (step S204), the CPU 2 proceeds to step S211.

If the command is determined to be the recording command in step S201, the CPU 2 suspends the reproduction (step S210). The reproduction process is thereby interrupted.

The CPU 2 outputs a recording permission

notification to the personal computer 12 (step S211), which accordingly transmits the content by packet transmission. The CPU 2 of the player 1 receives the packet data from the personal computer 12 (step S212).

5 The CPU 2 determines whether or not there is an end-of-content notification transmitted from the personal computer 12. If there is no end-of-content notification, the CPU 2 proceeds to step S213, where the CPU 2 outputs a data output standby command, then
10 records the data in the memory card 11 (step S214), proceeds to step S211, and repeats the same process.

When there remains no data to be received, the personal computer 12 transmits an end-of-content notification (step S215); then the CPU 2 proceeds to
15 step S216 and completes the recording. In step S217, as in step S201, the CPU 2 determines the command from the personal computer 12. If the command is the recording command, the CPU 2 proceeds to step S218, restarts the reproduction and returns to step S121. If
20 the command is the reproduction command, the CPU 2 returns to S121.

As described above, the player reproducing the stored content in the sixth embodiment is a content player capable of recording content by the connection
25 with external device for providing the content and of recording and reproducing different contents simultaneously, which determines whether or not the

current process condition of the player to know the load on receiving a recording requirement of the content from the external device. If the load is too heavy for the simultaneous execution of the reproduction and recording of different contents, a command is required for the external device. According to the command from the external device, the priority of the recording process and the reproduction process is determined to execute the processes in order of priority.

The embodiment is a portable audio player capable of the simultaneous execution of the recording and reproducing which can reproduce or record the content by remote control by the operation of only the external device connected with the player by means of a bi-directional communication cable. In this embodiment, if both the recording and the reproduction cannot be executed simultaneously, either the recording or the reproduction is selected and executed simultaneously according to the priority based on the command from the external device. Thus, unlike in the case of a conventional player, it is not necessary to interrupt the reproduction to record the content during the reproduction, or to interrupt the recording to reproduce the content during the recording. Therefore, it is possible to execute the recording and reproduction with an extremely easy operation.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the present invention in its broader aspects is not limited to the specific details, representative devices, and illustrated embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents. For example, the content is mainly audio data in the above embodiments, but other content such as moving images, still pictures and others can be treated similarly. In each of the above embodiments, USB cable was used to connect the player with a personal computer, but an interface corresponding to the plug and play capable of bi-directional communication and of recognizing the connection of the device such as IEEE 1394 may be employed. In each of the above embodiments, the content is recorded in the storage medium, and the way of reading what was recorded was described; it is possible to use the inside RAM and others for the purpose of recording or reproducing the content.

WHAT IS CLAIMED IS:

1. A recording and reproducing apparatus
comprising:

means for recording a content supplied from an
5 external device;

means for reproducing the content;

means for detecting that said reproducing means
performs a reproduction when a recording command is
issued; and

10 means for disabling said reproducing means and
enabling said recording means when said detecting means
detects that said reproducing means performs the
reproduction.

2. The apparatus according to claim 1, further
15 comprising means for enabling said recording means when
said detecting means does not detect that said
reproducing means performs reproduction.

3. The apparatus according to claim 1, further
comprising:

20 second detecting means for detecting that said
recording means is turned on when the recording command
is issued; and

means for turning on said recording means when
said second detecting means does not detect that said
25 recording means is turned on.

4. The apparatus according to claim 1, further
comprising means for restarting interrupted

reproduction after recording is completed.

5. A recording and reproducing apparatus comprising:

5 means for recording a content supplied from an external device;

means for reproducing the content;

means for detecting that the apparatus is connected to the external device;

10 means for setting an operation mode; and
means for controlling said recording means and said reproducing means in accordance with the operation mode when said detecting means detects that the apparatus is connected to the external device.

15 6. The apparatus according to claim 5, wherein said setting means sets one of a first mode, second mode, third mode, and fourth mode,

wherein in the first mode reproduction is continued if the apparatus is connected to the external apparatus during reproduction,

20 in the second mode reproduction is stopped and recording is started if the apparatus is connected to the external apparatus during reproduction,

25 in the third mode recording is started after reproduction is completed if the apparatus is connected to the external apparatus during reproduction, and

in the fourth mode reproduction is interrupted and recording is started if the apparatus is connected to

the external apparatus during reproduction and after recording is completed, the interrupted reproduction is restarted.

7. The apparatus according to claim 6, wherein
5 said setting means comprises an interface device for manually presetting the operation mode.

8. The apparatus according to claim 5, wherein said setting means comprises means for receiving a mode setting command from the external device.

10 9. A recording and reproducing apparatus comprising:

means for recording a content supplied from an external device;

15 means for reproducing the content, the reproducing means buffering content data before reproduction;

means for detecting that a sufficient amount of the content data is buffered when a recording command is issued during reproduction; and

20 means for enabling said recording means when said detecting means detects that the sufficient amount of the content data is buffered.

10. The apparatus according to claim 9, further comprising means for disabling said recording means when said detecting means does not detect that the
25 sufficient amount of the content data is not buffered.

11. The apparatus according to claim 10, further comprising means for keeping reproduction of said

turning on said recording means when it is not detected that said recording means is turned on.

20. The method according to claim 17, further comprising the step of restarting interrupted reproduction after recording is completed.

21. A method of controlling a recording and reproducing apparatus comprising means for recording a content supplied from an external device and means for reproducing the content, the method comprising the following steps of:

detecting that the apparatus is connected to the external device;

setting an operation mode; and

controlling said recording means and said reproducing means in accordance with the operation mode when said detecting means detects that the apparatus is connected to the external device.

22. The method according to claim 21, wherein said operation mode includes a first mode, second mode, third mode, and fourth mode,

wherein in the first mode reproduction is continued if the apparatus is connected to the external apparatus during reproduction,

in the second mode reproduction is stopped and recording is started if the apparatus is connected to the external apparatus during reproduction,

in the third mode recording is started after

5

10

15

20

25

enabling said recording means when said detecting means detects that the sufficient amount of the content data is buffered.

26. The method according to claim 25, wherein a recording is inhibited when it is not detected that the

sufficient amount of the content data is not buffered.

27. The method according to claim 26, wherein the reproduction is continued when it is detected that the sufficient amount of the content data is buffered.

5 28. The method according to claim 26, wherein the recording is started when it is detected that the sufficient amount of the content data is buffered.

29. The method according to claim 25, further comprising the step of setting an operation mode; and
10 wherein said recording means and said reproducing means is controlled in accordance with the operation mode when it is detected that the sufficient amount of the content data is not buffered.

30. The method according to claim 29, wherein the
15 operation mode includes a first mode, second mode, third mode, and fourth mode,

 wherein in the first mode reproduction is continued if the apparatus is connected to the external apparatus during reproduction,

20 in the second mode reproduction is stopped and recording is started if the apparatus is connected to the external apparatus during reproduction,

 in the third mode recording is started after reproduction is completed if the apparatus is connected
25 to the external apparatus during reproduction, and

 in the fourth mode reproduction is interrupted and recording is started if the apparatus is connected to

the external apparatus during reproduction and after recording is completed, the interrupted reproduction is restarted.


31. The method according to claim 29, wherein said
5 setting step comprises a substep of setting the
operation mode using a manual interface device.

32. The method according to claim 29, wherein said setting means comprises a substep of receiving a mode setting command from the external device.

ABSTRACT OF THE DISCLOSURE

The present invention comprises a communicating means to communicate with external device providing content, a storage medium retaining the content capable
5 of recording and reading the content, recording and reproducing means which record the content obtained by means of the communicating means in the storage medium and which read and reproduce the content recorded in the storage medium, a recording operation means to
10 execute a recording operation, control means which judge the recording and reproducing process conditions when the recording operation means is operated, and if the content is reproduced, after stopping the reproduction, while if the content is not reproduced,
15 immediately, control the content received by means of the communicating means so as to be recorded in the storage medium.








FIG. 4





FIG. 5



I declare further that my post office address is at c/o Intellectual Property Division, KABUSHIKI KAISHA TOSHIBA, 1-1 Shibaura 1-chome, Minato-ku, Tokyo 105-8001, Japan; and that my citizenship and residence are as stated below next to my name:

Inventor: (Signature)

Date _____

Residence

Tadahiro Aihara

Tadahiro Aihara

Date: Sep. 1, 2000

Citizen of: Japan

Hachioji-shi, Japan

Takafumi Ito

Takafumi Ito

Date: Sep. 1. 2000

Citizen of: Japan

Ome-shi, Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

Date:

Citizen of: Japan

00S0567

Residence

Hachioji-shi, Japan

Ome-shi, Japan

Takafumi Ito

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

1300 I Street, N. W.,
Washington, D. C. 20005-3315